



1101 McKinley Street  
Anoka, MN 55303  
Phone (763) 786-6682  
Fax (763) 786-2167  
www.polycam.com

Part Name: C-900 Pulling Head (Diamond-Loc/Eagle-Loc)  
Part Number: 656-xxxx



### **General Design**

The Poly-Cam steel pulling heads are constructed with a single-eye rated to the safe pulling strength of the pipe installed.

For further information please contact your Poly-Cam distributor or representative.

### **Features**

- Size range from 4" - 12" diameter
- Round nose design for ease of pulling
- Strong steel construction for longevity

### **System Performance**

The transition fitting is designed to handle full pressure with a 2:1 safety factor at 73.40 degrees Fahrenheit with a minimum 50 year design life.

### **Quality Assurance**

The transition fitting shall be manufactured by Poly-Cam, Inc. Poly-Cam, Inc. shall provide quality assurance with regards to proper installation, compatibility, performance, and acceptance.

### **Installation**

Find installation guide at:

<https://poly-cam.com/products/pulling-heads/series-656-c-900-pulling-head-diamond-loc-eagle-loc/>

# Series 656 C-900 Pulling Head (Diamond-Loc/Eagle-Loc)

Nominal Size (In.)	Pulling Head Diameter <b>A</b>	Pulling Head Length <b>B</b>	Eye Hole <b>C</b>	Pulling Head Inside <b>D</b>	Pin Hole <b>E</b>	Number of Holes
4	5.56	13	1.5	4.86	0.375	16
6	7.5	17.7	2	6.90	0.5	16
8	9.75	18.7	2	9.12	0.5	16
10	12.75	21.625	2	11.15	0.5	16
12	14	22	2	13.3	0.5	20

