



Series 575

Electrofusion Tapping Saddle with CC Thread

Available In:

Aluminum Bronze

304 Stainless Steel

316 Stainless Steel

Standard SDR Sizes 7, 9, 11, 17

Fully Pressure Rated



Nominal Main Size (In.)	Poly-Cam Thread Material	Female CC Thread Outlet A	Outlet to Main Length B	IPS Radius R	DIPS Radius R2
2	C954 Bronze, Stainless 316, Stainless 304	.75-2"	4.75	2.375	NA
3	C954 Bronze, Stainless 316, Stainless 304	.75-2"	4.75	3.5	NA
4	C954 Bronze, Stainless 316, Stainless 304	.75-2"	4.75	4.5	4.8
6	C954 Bronze, Stainless 316, Stainless 304	.75-2"	4.75	6.625	6.9
8	C954 Bronze, Stainless 316, Stainless 304	.75-2"	4.75	8.625	9.05
10	C954 Bronze, Stainless 316, Stainless 304	.75-2"	4.75	10.75	11.1
12	C954 Bronze, Stainless 316, Stainless 304	.75-2"	4.75	12.75	13.2
14	C954 Bronze, Stainless 316, Stainless 304	.75-2"	4.75	14	15.3
16	C954 Bronze, Stainless 316, Stainless 304	.75-2"	4.75	16	17.4
18	C954 Bronze, Stainless 316, Stainless 304	.75-2"	4.75	18	19.5
20	C954 Bronze, Stainless 316, Stainless 304	.75-2"	4.75	20	21.6
22	C954 Bronze, Stainless 316, Stainless 304	.75-2"	4.75	22	NA
24	C954 Bronze, Stainless 316, Stainless 304	.75-2"	4.75	24	25.8

