



Series 578

Electrofusion Tapping Saddle with Groove Transition

Available In:

Carbon Steel

304 Stainless Steel

316 Stainless Steel

Standard SDR Sizes 7, 9, 11, 17

Fully Pressure Rated



Nominal Main Size (In.)	Poly-Cam Groove Material	Groove Outlet A	Outlet to Main Length B	IPS Radius R	DIPS Radius R2
3	Carbon Steel, Stainless 316, Stainless 304	0.5-1.25"	6	3.500	N/A
4	Carbon Steel, Stainless 316, Stainless 304	0.5-1.5"	6	4.500	4.800
6	Carbon Steel, Stainless 316, Stainless 304	0.5-2"	7	6.625	6.900
8	Carbon Steel, Stainless 316, Stainless 304	0.5-3"	8	8.625	9.050
10	Carbon Steel, Stainless 316, Stainless 304	0.5-4"	9	10.750	11.100
12	Carbon Steel, Stainless 316, Stainless 304	0.5-6"	11	12.750	13.200
14	Carbon Steel, Stainless 316, Stainless 304	0.5-8"	11	14.000	15.300
16	Carbon Steel, Stainless 316, Stainless 304	0.5-8"	12	16.000	17.400
18	Carbon Steel, Stainless 316, Stainless 304	0.5-8"	16	18.000	19.500
20	Carbon Steel, Stainless 316, Stainless 304	0.5-8"	18	20.000	21.600
24	Carbon Steel, Stainless 316, Stainless 304	0.5-8"	20	24.000	25.800
30	Carbon Steel, Stainless 316, Stainless 304	0.5-8"	20	30.000	32.000

