

ID Control Threaded Transition

Available In:

- Carbon Steel Epoxy-Coated**
- Aluminum Bronze**
- 304 Stainless Steel**
- 316 Stainless Steel**

Standard SDR Sizes 7, 9, 11, 17

Import or Domestic

Fully Pressure Rated



Nominal Size (In.)	HDPE/ Steel Pipe O.D. A	Steel Pipe I.D. B	Steel Length C	Thread Length D	Compression Ring Length E	SDR 11 HDPE I.D. F	Compression Ring O.D. SDR 11 G
0.5	0.840	0.622	2.5	0.78	1.5	0.680	~1.03
0.75	1.050	0.824	3	0.8	2	0.850	~1.29
1	1.315	1.049	3	0.98	2	1.060	~1.62
1.25	1.660	1.380	3.5	1.01	2	1.340	~2.04
1.5	1.900	1.610	4.5	1.03	2.5	1.530	~2.34
2	2.375	2.067	4.5	1.06	3.5	1.917	~2.84
2.5	2.875	2.469	5	1.57	3.5	2.321	~3.41
3	3.5	3.068	5.5	1.63	5	2.826	~4.14
4	4.5	4.026	5.5	1.73	5.5	3.633	~5.44
6	6.625	6.065	9	1.84	8	5.349	~8.0
8	8.625	7.981	12	1.95	10	6.963	~10.3
10	10.75	10.02	12	2.15	12	8.679	~12.9
12	12.75	12	12	2.36	12	10.29 3	~15.3

