



1101 McKinley Street  
Anoka, MN 55303  
Phone (763) 786-6682  
Fax (763) 786-2167  
www.polycam.com



Part Name: Reducing Extra Heavy ID-Controlled Weld-On Transition Fitting  
Part Number: 865-xxxx

### **Reducing Extra Heavy ID Controlled Weld-On Transition Fitting**

**Description** - The Poly-Cam ID-Controlled Weld-On is designed to provide a smooth, interior transition between the steel pipe and the polyethylene pipe. The connection between the steel fitting and the polyethylene pipe is accomplished with a multi-level barb system and a compression ring supporting the connection. The multi-level barb system provides the sealing connection between the steel and the polyethylene pipe. The interior of the fitting contains no sharp edges in which pipeline cleaning pigs can be caught or damaged. The weld-on is coated with an epoxy coating. The compression ring is constructed out of carbon steel material and coated with an epoxy-coated material. Stainless steel compression rings are optional.

The Poly-Cam ID-Controlled Weld-On is a custom design fitting allowing the installer to transition from one specific type steel materials to a specific type of polyethylene pipe.

Tested and complies to ASTM D2513, ASTM 1973-05, D1599, D1598

#### **Steel Material Options:**

- A53B ERW Carbon Steel / A106 Seamless Carbon Steel  
Available in the following upon request and subject to availability:  
X42, X52, X60, X65, X70, API 5L, NACE MR0175, A333 Grade 6
- 304 Stainless Steel
- 316 Stainless Steel

#### **Polyethylene Pipe Options:**

- PE 3408 ASTM F-714
- PE 3408 ASTM 2513 Gas Pipe
- PE 2406
- PE 4710

Additional options are available.

#### **Epoxy Coated Material:**

- Color HB, Red Oxide, IF1947T or Green 3M™ Scotchkote™ Fusion-Bonded Epoxy Coating 6233

# Series 865 Reducing Extra Heavy ID Controlled Weld-On (A53/A106)

## SDR 7

Nominal Size (In.)	Steel Pipe O.D. <b>A</b>	Steel Pipe I.D. <b>B</b>	Steel Length <b>C</b>	HDPE Pipe Length <b>D</b>	Compression Ring Length <b>E</b>	SDR 7 HDPE I.D. <b>F</b>	HDPE O.D. <b>G</b>
3x2	2.375	1.939	12	24	3.5	2.440	3.500
4x2	2.375	1.939	12	24	3.5	3.137	4.500
4x3	3.5	2.9	14	24	5	3.137	4.500
6x4	4.5	3.826	14	24	5.5	4.619	6.625
8x6	6.625	5.761	20	30	8	6.013	8.625
10x8	8.625	7.625	22	30	10	7.494	10.75
12x8	8.625	7.625	22	30	10	8.889	12.75
12x10	10.75	9.75	26	40	12	8.889	12.75
14x10	10.75	9.75	26	40	12	9.760	14
14x12	12.75	11.75	28	40	12	9.760	14
16x12	12.75	11.75	28	40	12	11.154	16
16x14	14	13	28	40	12	11.154	16
18x12	12.75	11.75	28	40	12	12.549	18
18x14	14	13	28	40	12	12.549	18
18x16	16	15	28	48	14	12.549	18
20x14	14	13	28	40	12	13.943	20
20x16	16	15	28	48	14	13.943	20
20x18	18	17	28	48	14	13.943	20
22x18	18	17	28	48	14	15.337	22
22x20	20	19	28	48	15	15.337	22
24x18	18	17	28	48	14	16.731	24
24x20	20	19	28	48	15	16.731	24

