



# Series 577

## Electrofusion Tapping Saddle with FPT Thread

**Available In:**

**Aluminum Bronze**

**Carbon Steel**

**304 Stainless Steel**

**316 Stainless Steel**

**Standard SDR Sizes 7, 9, 11, 17**

**Fully Pressure Rated**



Nominal Main Size (In.)	Poly-Cam Thread Material	Female Pipe Thread Outlet A	Outlet to Main Length B	IPS Radius R	DIPS Radius R2
1.25	Carbon Steel, C954 Bronze, Stainless 316, Stainless 304	0.5-1.25"	4.5	1.660	N/A
1.5	Carbon Steel, C954 Bronze, Stainless 316, Stainless 304	0.5-1.5"	5	1.900	N/A
2	Carbon Steel, C954 Bronze, Stainless 316, Stainless 304	0.5-2"	6	2.375	N/A
3	Carbon Steel, Stainless 316, Stainless 304	0.5-2"	8	3.500	N/A
4	Carbon Steel, Stainless 316, Stainless 304	0.5-2"	8	4.500	4.800
6	Carbon Steel, Stainless 316, Stainless 304	0.5-2"	9	6.625	6.900
8	Carbon Steel, Stainless 316, Stainless 304	0.5-2"	8	8.625	9.050
10	Carbon Steel, Stainless 316, Stainless 304	0.5-2"	9	10.750	11.100
12	Carbon Steel, Stainless 316, Stainless 304	0.5-2"	10	12.750	13.200
14	Carbon Steel, Stainless 316, Stainless 304	0.5-2"	10	14.000	15.300
16	Carbon Steel, Stainless 316, Stainless 304	0.5-2"	10	16.000	17.400
18	Carbon Steel, Stainless 316, Stainless 304	0.5-2"	10	18.000	19.500

